


8542 10



**LOWE'S**

**SANITARY**  
**KALSOMINE**

**TINTS AND COLORS**

Ready for Use  
after mixing with  
cold or hot water.

*The Lowe Brothers Co.*

DAYTON, OHIO

BOSTON NEW YORK JERSEY CITY CHICAGO

KANSAS CITY MINNEAPOLIS ATLANTA

G. G. GIFFORD,

W. TISBURY, MASS.

# Lowe's SANITARY KALSOMINE

---

## Preparing the Walls

Before applying this kalsomine to any surface, care should be taken that all dirt and any old or peeling kalsomine is very thoroughly washed off, and any loose oil paint or other material previously applied to the wall well scraped and removed; particularly any limewash, which is liable to destroy delicate tints.

All holes and cracks in plastered walls should be filled with Plaster of Paris with some dry kalsomine added.

When walls and ceilings have excessive suction, it is advisable to apply a coating of Lowe's Wall Size. It stops Suction, neutralizes Lime, kills Stains, Saltpetre and Efflorescence, and gives kalsomine the proper tooth to grip, work smoothly and stay put. Allow the Size to dry thoroughly before applying Kalsomine.

A small quantity of liquid Lowe's Wall Size added to kalsomine prevents clouding and streaking during unfavorable weather.

## Directions for Mixing

Add sufficient cold water (hot water may be used if desired) to the dry powder to make an ordinary thick paste. Stir thoroughly until free from lumps and then thin down with cold water to the consistency of oil paint or cream.

---

These samples are made by spreading the actual material on paper with a wall brush. Always order by number.

## Directions for Applying

To be sure of good results, the air in the room should be dry and of moderate temperature. Close the windows and doors to avoid draughts.

The kalsomine should be flowed on freely with a good kalsomine brush, but must not be rubbed out like oil paint.

After application open all windows and doors to allow free circulation of air and make a fire if necessary, as quick drying is essential to good work.

## Lowe's Sanitary Kalsomine

This kalsomine is the ideal Wall Coating for the decoration of all interiors. It gives that soft, velvety, water-color effect so essential to refined surroundings and can be applied on plaster walls, wood, or any of the various wall boards.

This kalsomine is made under the famous formula that has set the standard in the manufacture of Wall Coatings for over a quarter of a century.

It is manufactured from selected materials, scientifically compounded in dry powder form, so that it only requires mixing with ordinary cold water to prepare it for immediate use.

This kalsomine is milled in white, attractive tints and rich deep colors, all of which are intermixable, so that any desired shade may be produced.

It is adaptable to the individual decorative requirements of any class of building and harmonizes perfectly with any style of furnishings.



I-1




I-2



I-3



I-4



I-5



I-6



I-7



I-8





L-9



L-10



L-11



L-12



L-13



L-14



L-15



L-16



**LOWE'S**

**SANITARY**  
**KALSOMINE**

**TINTS AND COLORS**

Ready for Use  
after mixing with  
cold or hot water.

*The Lowe Brothers Co.*  
DAYTON, OHIO

BOSTON NEW YORK JERSEY CITY CHICAGO  
KANSAS CITY MINNEAPOLIS ATLANTA

Digitized by ASSOCIATION FOR PRESERVATION TECHNOLOGY, [www.apti.org](http://www.apti.org) for the  
BUILDING TECHNOLOGY HERITAGE LIBRARY

<https://archive.org/details/buildingtechnologyheritagelibrary>

From the collection of

Tulane University: Southeastern Architectural Archive <http://seaa.tulane.edu>